

## TECHNICAL DATA SHEET

15.01.2024 REV.3

### IRON MICA 106

#### PRODUCT

Spraypaint with micaceous finish, fast drying.

#### PROPERTIES AND FIELDS OF USE

Easy to use paint. Resistant and covering, gives a micaceous finish. For indoor and outdoor. Excellent resistance to atmospheric agents and light. Excellent anti-rust properties.

Ideal for: INDUSTRY, CONSTRUCTION, CRAFTS, DIY.

#### SURFACES

High adhesion on numerous supports such as metal (iron, brass, steel), ABS plastics (no PP or similar), wood, glass, stone, cement.

Incompatibility: do not apply on surfaces with residues of products containing silicones. Do not apply on polystyrene.

#### TECHNICAL SPECIFICATIONS

Binder	Modified alkyd
Yield	1,5-2 m <sup>2</sup>
Pressure at 20 °C	from 4.2 to 4,8 bar
Pressure at 50 °C	from 7.6 to 8.4 bar
COV	see SDS Sec. 9.1 and 15.3
Maximum temperature:	80-100°C
Drying time:	
Dust-free	10-15 minutes
Dry to touch	30-40 minutes
Deep dry	25-30 hours

#### INSTRUCTIONS FOR USE

**Before use carefully read the instructions on the can and consult the SDS for safe handling of the product (Sec. 7.1).**

Use between 10 and 25 °C on surfaces at the same temperature, in well ventilated environments. Mask the parts not to be treated. Remove residues of rust or paint not anchored. Degrease. Shake the can vigorously for approx. 2 minutes from the moment you feel the mixing balls. Make a spray test on a separate surface. Spray a layer in cross coats, from a distance of 20-25 cm. If necessary repeat the application after about 15 minutes. On plastics we recommend the use of the special primer. To level the surfaces use the filler base in advance. Every time you finish the application, turn the can upside down and spray for a few seconds until the product comes out so you can clean the valve and spray head.

**For further information refer to the SDS: labelling (Sec. 2.2), storage (Sec. 7.2) and disposal (Sec. 13).**



*Sede Legale, Amministrativa e Operativa: Via Benvenuto Cellini 26, 20033 Solaro (Mi)*

*C.C.I.A.A. Milano 1172121*

*Codice fiscale e Partita IVA: 01485370124*

*Capitale sociale: Euro 1.000.000,00 interamente versato*

*Contacts: Phone: +39 02 9690664 Fax: +39 02 9691714*

*Website: [www.colorpack.com](http://www.colorpack.com) Email: [info@colorpack.com](mailto:info@colorpack.com)*

*SDI CODE: BY5KTZZ*

## EXEMPTION FROM LIABILITY

The information contained in this document is provided to the best of our scientific knowledge. However, they should be regarded as non-binding indications and do not release the consumer from personally carrying out checks on the products as to their compatibility with their intended uses. Colorpack Srl is relieved of any liability if any damage is not link to specific causes attributable to the same Colorpack Srl.

THE LABORATORY/QMS



**Sede Legale, Amministrativa e Operativa:** Via Benvenuto Cellini 26, 20033 Solaro (Mi)

**C.C.I.A.A.** Milano 1172121

**Codice fiscale e Partita IVA:** 01485370124

**Capitale sociale:** Euro 1.000.000,00 interamente versato

**Contacts:** Phone: +39 02 9690664 Fax: +39 02 9691714

Website: [www.colorpack.com](http://www.colorpack.com) Email: [info@colorpack.com](mailto:info@colorpack.com)

SDI CODE: **BY5KTZZ**