**TECHNICAL DATA SHEET**

*04.01.2024 REV.0*

# SANITARY 600

## PRODUCT
Enamel with sanitary finish, non-yellowing, fast drying.

## PROPERTIES AND FIELDS OF USE
Fast drying enamel, easy to use, with finishes of the colors of the sanitary ware. Resistant and opaque, gives brilliant lacquers. For indoor and outdoor use. Excellent resistance to atmospheric agents and light. Particularly resistant to water. Over-varnishable.
Ideal for: CRAFT, DIY.

## SURFACES
High adhesion on numerous supports such as ceramic, metal (iron, brass, steel), ABS plastics (no PP or similar), wood, glass, stone, cement. For plastic surfaces, apply the plastic primer beforehand. Incompatibility: do not apply on surfaces with residues of products containing silicones. Do not apply on polystyrene. Application on synthetic paints is not recommended.

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Binder | Modified acrylic |
| Yield | 1,5-2 $m^2$ |
| Pressure at 20 ºC | Da 4.2 a 4,8 bar |
| Pressure at 50 ºC | Da 7.6 a 8.4 bar |
| COV | see SDS Sec. 9.1 and 15.3 |
| Gloss level: | |
| Gloss | 80-85 gloss at 60° |
| Maximum temperature: | 90-100°C |
| Drying time: | |
| Dust-free | 5-8 minutes |
| Dry to touch | 15-20 minutes |
| Deep dry | 16-20 hours |

## INSTRUCTIONS FOR USE
**Before use carefully read the instructions on the can and consult the SDS for safe handling of the product (Sec. 7.1).**
Use between 10 and 25 ºC on surfaces at the same temperature, in well ventilated environments. Mask the parts not to be treated. Remove residues of rust or paint not anchored. Degrease. Shake the can vigorously for approx. 2 minutes from the moment you feel the mixing balls. Make a spray test on a separate surface. Spray a layer in cross coats, from a distance of 20-25 cm. If necessary repeat the application after about 15 minutes. On plastics we recommend the use of the special primer. To level the surfaces use the filler base in advance. Every time you finish the application, turn the can upside down and spray for a few seconds until the product comes out so you can clean the spray-head.

***Sede Legale, Amministrativa e Operativa:*** *Via Benvenuto Cellini 26, 20033 Solaro (Mi)*
***C.C.I.A.A.*** *Milano 1172121*
***Codice fiscale e Partita IVA:*** *01485370124*
***Capitale sociale****: Euro 1.000.000,00 interamente versato*
***Contacts:*** *Phone: +39 02 9690664 Fax: +39 02 9691714*
*Website: www.colorpack.com Email: info@colorpack.com*
*SDI CODE:* ***BY5KTZZ***

**For further information refer to the SDS: labelling (Sec. 2.2), storage (Sec. 7.2) and disposal (Sec. 13).**

## EXEMPTION FROM LIABILITY

The information contained in this document is provided to the best of our scientific knowledge. However, they should be regarded as non-binding indications and do not release the consumer from personally carrying out checks on the products as to their compatibility with their intended uses. Colorpack Srl is relieved of any liability if any damage is not link to specific causes attributable to the same Colorpack Srl.

THE LABORATORY/QMS

***Sede Legale, Amministrativa e Operativa:*** *Via Benvenuto Cellini 26, 20033 Solaro (Mi)*
***C.C.I.A.A.*** *Milano 1172121*
***Codice fiscale e Partita IVA:*** *01485370124*
***Capitale sociale****: Euro 1.000.000,00 interamente versato*
***Contacts:*** *Phone: +39 02 9690664 Fax: +39 02 9691714*
*Website: www.colorpack.com Email: info@colorpack.com*
*SDI CODE:* ***BY5KTZZ***